

TECHNICAL DATA SHEET

Satin Latex Reusable Glove



PRODUCT INFORMATION

- ✓ Natural Rubber
- ✓ Unlined
- ✓ Length 330 ± 10
- ✓ Thickness $0,45 \pm 0,03$
- ✓ Size S M L XL
- ✓ Colour: natural
- ✓ AQL 1.5
- ✓ Conformity: ASTM D4679



Medical



Food industry



Industry



Automotive



Cleaning

APPLICATIONS AND USES

- ✓ It is important to note that latex gloves can cause allergic reactions. In case of allergy, consult a doctor immediately.
- ✓ Before putting on the gloves, make sure they are free of defects; place your hand inside and gently pull them on.
- ✓ Store them in a cool, dry place, protected from light.
- ✓ They are intended for single use only and must be disposed of in an environmentally friendly manner in appropriate waste disposal containers in accordance with current regulations.

LEGAL REGULATIONS

Category III: Personal Protective Equipment (PPE) according to EU Regulation 2016/425, whose standards are: EN 21240:2020, EN 374-1:2016+A1: 2018 Type B, EN 374-4:2019, EN 374-5:2016.

TECHNICAL SPECIFICATIONS

Reference	Size	Polybag	Units per carton	Length in mm	Width in mm	Minimum thickness in mm	
						Finger	Palma
10702	S	1 pair	144 pairs	300 ± 10	95 ± 5	29 ± 3	45 ± 3
10703	M	1 pair	144 pairs	300 ± 10	105 ± 5	31 ± 3	45 ± 3
10704	L	1 pair	144 pairs	300 ± 10	110 ± 5	33 ± 3	45 ± 3
10705	XL	1 pair	144 pairs	300 ± 10	120 ± 5	36 ± 3	45 ± 3

Property	Unit of measurement	Typical value	Test method
Resistance	Mpa	>17	ASTM D412
Tensile strength	%	650 - 750	ASTM D413