

OCEANFACE 38

REUSABLE | NITRILE | BLUE | S - XL | SATIN



Reusable satin nitrile glove with 0.38 mm thickness, designed for high sensitivity, grip, and chemical resistance. Ideal for cleaning, food processing, chemical handling, and demanding tasks. Offers durability and reliable protection in every use.

FEATURES:

- ✓ Non-slip pattern for secure grip in dry and wet conditions
- ✓ Food-contact safe
- ✓ Reinforced material for enhanced protection
- ✓ Manufactured under strict quality management
- ✓ Excellent abrasion resistance
- ✓ Straight cuff

SPECIFICATIONS

- ✓ Material: Nitrile rubber
- ✓ Thickness: 0.38 ± 0.05 mm
- ✓ Cuff: Straight
- ✓ Lining: Chlorinated, unlined
- ✓ Treatment: Chlorination
- ✓ Exterior: Smooth finish
- ✓ Colors: Blue



Labelling: expiry date, date of manufacture, batch number, reference number, barcode. Instructions for use in several languages: Spanish, English, French, Portuguese.

Reference	Size	Individual Packing	Units per Carton
10732	7	1 pair	144 pairs
10733	8	1 pair	144 pairs
10734	9	1 pair	144 pairs
10735	10	1 pair	144 pairs

Shelf Life: 5 years

Glove dimensions	S	M	L	XL
Length	Min 330 mm	Min 330 mm	Min 330 mm	Min 330 mm
Palm thickness mm (± 0,02)	0,38	0,38	0,38	0,38

PACKING




REGULATIONS

The product is classified as category III personal protective equipment (PPE) under the EU PPE Regulation 2016/425 and has been shown to comply with this regulation through harmonised European standards EN ISO 21420:2020, EN 388:2016+A1:2018, EN ISO 374-1:2016+A1:2018 and EN ISO 374-5:2016.

PROTECTION AGAINST CHEMICAL RISKS

EN ISO 374-1:2016+A1:2018 Type A



AJTKLMNOPST

Methanol (A)
Hydrogen peroxide 30% (P)
Hydrogen acid 40% (S)
Diethylamine (G)
n-Heptane (J)
Formaldehyde 37% (T)
Sodium hydroxide 40% (K)
Sulphuric acid 96% (L)
Nitric acid 65% (M)
Acetic acid 99% (N)
Ammonium hydroxide 25% (O)


Level

EN ISO 374-4:2019
Degradation %

2	76.9
6	1.2
4	x
1	82.4
6	10.6
6	-20.1
6	-23.5
4	49.7
3	94.8
3	81.4
5	13.9

PROTECTION AGAINST MECHANICAL RISKS

EN 388:2016+A1:2018



3101X

(Mechanical risks 3101X)

Resistance to abrasion:
Blade cut resistance:
Tear resistance:
Puncture resistance:
TDM cut resistance:

Level

3
1
0
1
X

PROTECTION AGAINST THE RISK OF MICRO-ORGANISMS

EN ISO 374-5:2016



VIRUS

Protection against bacteria and fungi:
Protection against viruses:

Pass
Pass